



Wood Pellet Bin

Accessories:

Accessories available on request include Cam Lock Assembly, Filter Sock, and Outlet boxes complete with slide valves.



JFC recommends that the bin sits on a level concrete base at ground level 2.5m x 2.5m with no less than 100mm of 30N concrete.

The Bin is to be secured to base using 4 x anchor points which also earths the bin preventing static build up.

JFC Manufacturing Co Ltd

Weir Road, Tuam, Co Galway, Ireland

Tel: (+) 353 (0)93 24066

Fax: (+) 353 (0)93 24923

Web: www.jfc.ie

Email: info@jfc.ie

JFC Manufacturing (Europe) Ltd.

Maes Y Clawdd Industrial Estate,
Maesbury Road, Oswestry, Shropshire,
SY10 8NN, UK

Tel: (+) 44 (0) 1691 659226

Fax: (+) 44 (0) 1691 659344

Web: www.jfcuk.com

Email: info@jfcuk.com



Auger Feed



Manual Feed

JFC Pellet Bin includes:

- Service Box Suitable for 45° auger and vacuum discharge systems
- Manual Discharge for bucket filling. Fitted as standard
- Anti Static system
- Sight glass
- Refill Order Level Plate
- Bin comes pre-assembled (All Components included)

JFC Wood Pellet bin is waterproof and condensation free, making it the ideal solution for storing wood pellets externally

Dimensions: Ø2.05m x H2.7m

Capacity: 3.3 Tonne

Volume: 5 Cubic Meters

Code: WPB-3T

It is believed that the information and dimensions given in this publication are correct. The products marketed by the company are, however subject to continuous development and the company, therefore reserves the right to alter information without notice. Copyright JFC 2008 © WPB September 08.



www.jfc.ie



Wood Pellet Bin



Waterproof top access port allows internal inspection and bag filling.



Each bin comes complete with a manual discharge valve for bucket filling. Check-chain also fitted for additional security.



Augers and vacuum systems can be fitted with ease using horizontal and angled location sockets. Lockable shut off valve allows service box to be maintained with ease.



Top Lid can be easily rotated in 60 degree segments to cater for left and right-handed situations and also allowing easy access to bulk fittings at all times. JFC Bin when assembled is 100% watertight. Fixed Gasket is used to seal joint of bin preventing any dust from escaping whilst filling.



As standard a "Reorder Level Plate" is fitted inside the bin. This reorder level indicator plate can be viewed through the sight glass in the mid-section of the bin. This plate indicates an approx. content of 250kg left in the bin so that you can reorder your fill of pellet.



REFILL LEVEL -